



boxed low voltage  
emergency pack

# Remergy

 **20 watt**

 **12 volts**

## Product Description

The Remergy boxed low voltage emergency pack will adapt a standard low voltage tungsten halogen luminaire to operate in emergency mode. The installer friendly one piece emergency pack contains both module and battery.

## Product Features

- **Maintained (M) and non-maintained (NM) versions available to suit the requirement**
- **Can be mounted up to 15 metres from the fitting**
- **Thermal overload protection with fused input and output for maximum reliability**
- **Deep discharge protection as standard to protect the service life of the battery**
- **Green LED charge indicator supplied with one metre of lead for remote mounting or for fixing within the luminaire bezel**
- **Cool running solid state constant current charger**
- **High capacity VRLA valve regulated lead acid batteries**
- **Can be supplied with or without integral transformer**
- **Rugged corrosion resistant ventilated galvanised steel box with 20mm cable entries and key hole fixing slots**
- **Guaranteed for three years**
- **Three hour duration in the event of a mains failure**



# Remergy

boxed low voltage emergency pack

20 watt 12 volts

## Types

- Non Maintained – The pack will operate the downlighter in the event of a mains failure only
- Maintained – The pack will operate the downlight in normal and emergency mode and is complete with transformer

## Specification


- Operating voltage : 190 - 265 AC
- AC input: 60mA max, 12mA standby
- Recharge Period: 24 hours
- Constant output for entire period
- Automatic trickle charge, current limited and constant voltage
- Auto chagerover to and from emergency mode according to IEC598
- Charging current 900mA, 10mA floating
- VRLA battery management circuit

## Standards

Designed and manufactured to:  
BSEN 60598.2.22

## Module Dimensions

Part No.	Length	Width	Height	Fixing A	Fixing B
EZX12/20	254mm	215mm	80mm	172mm	198mm



## Mamimum Cable Runs

Part No.	1mm	1.5mm	2.5mm	4.0mm	6mm
EZX12/20	3m	5m	10m	15m	15m


## Accessories

EZ/LH, Remote LED housing




## Typical Wiring Diagram


### Typical Wiring Diagrams



**EZX-NM3**  
Non-maintained mode



**EZX-M3**  
Maintained mode with integral transformer



**EZX-NM3**  
Maintained mode with remote transformer

## Order Codes

Part Number	Load	Battery	Battery Type	BLF	Mode	Ambient Temperature	Duration	Weight
EZX 12/20/NM3	12v 20w	12V 7AH	VRLA	100%	NM	25°C	3	5.5Kg
EZX 12/20/M3	12v 20w	12V 7AH	VRLA	100%	M*	25°C	3	5.5Kg

\*Maintained version supplied with an integral dimmable electronic transformer.

**escapezone**

**escapezone Ltd**  
Unit 23, Red Lion Business Centre  
Red Lion Road, Surbiton, Surrey KT6 7QD  
Tel: 0208 391 9001 Fax: 0208 391 9002  
Email: sales@escapezone.net  
Web: www.escapezone.net